

bproauto® DOT 3 brake fluid

Superior braking and wear protection

bproauto® DOT 3 brake fluid is formulated with polyalkylene glycol ethers, plus lubricity additives and corrosion inhibitors. It is suitable for use in hydraulic clutch systems and is fully compatible with other fluids meeting FMVSS 116 DOT 3, DOT 4 and DOT 5.1.

Protects against wear, rust and corrosion

- High boiling point protects against wear and corrosion
- Prolonged service life of brake system components



Storage: All packages should be stored under cover. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Applications

- bproauto DOT 3 brake fluid is designed for use in the hydraulic brake and clutch systems of passenger cars and commercial vehicles except in systems for which a mineral oil-based fluid is recommended

Recommendations for use

- Fluid should be changed according to the vehicle manufacturer or after 1 year of use
- To maintain superior performance, avoid mixing with non-bproauto brake fluid products
- Avoid spilling on paint work. In case of spillage, rinse the affected area with water immediately. **Do not wipe.** Check Owner's Operator's Manual for details.

Specifications and approvals

- bproauto DOT 3 brake fluid is a high boiling brake fluid and meets the requirements of:
SAE J1703
FMVSS 116 DOT 3
ISO 4925 Class 3
JASO JIS K2233 Class 3

Partner with bproauto parts to provide your customers with maximum wear protection and superior braking performance.