

bproauto[®] DOT 4 high performance hydraulic brake fluid.

Safe braking under pressure

bproauto[®] DOT 4 brake fluid is an extra high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems. Our unique formulation is based on polyethylene glycol ether technology to provide the highest level of brake and clutch performance in modern as well as older model automotive and commercial vehicles.

Protects against wear, rust and corrosion

- **High boiling point:** Consistent, safe brake performance under severe braking pressure
- **Minimum rubber component swell:** Reduces leakage and loss of fluid

Applications

- bproauto DOT 4 brake fluid is recommended for use in applications requiring disc, drum and anti-skid braking systems used in average to high performance vehicles requiring DOT 3 or DOT 4 level performance

Recommendations for use

- Use only in its concentrated form out of a previously unopened or well-sealed container
- Always seal the container immediately after use as the fluid rapidly absorbs moisture from the atmosphere; this will reduce service life significantly
- Never reuse drained brake fluid
- Brake fluid can affect the vehicle paintwork; remove spills immediately without rubbing
- Brake fluid should be drained from the vehicle every two years or 40,000 km (24,000 miles) and refilled

Check Owner's Operator's Manual for details.



Specifications and approvals

FMVSS 116 DOT 3
FMVSS 116 DOT 4
ISO 4925:2005 Class 3
ISO 4925:2005 Class 4
SAE J1704

Partner with bproauto parts to provide your customers with maximum wear protection and superior braking performance.