

bproauto[®] DOT 5.1 **100% synthetic brake fluid**

Excellent anti-corrosion properties

Specifically designed for anti-lock brake systems (ABS)!

bproauto[®] DOT 5.1 is a 100% synthetic, glycol-based brake fluid for hydraulic actuated brake and clutch systems, as well as other electronic stability (ESP, ASR) programs. The unique DOT 5.1 formulation is designed to **maintain easy fluid circulation even in extreme cold temperatures.**

Long life and easy flow for better braking response

- **High wet boiling point:** Consistent, safe brake performance
- **Formula is neutral with seals:** Reduces leakage and loss of fluid

Applications

- bproauto DOT 5.1 brake fluid is recommended for all types of hydraulic actuated brake and clutch systems requiring fluids meeting DOT 3, DOT 4 or DOT 5.1 specifications per manufacturers' recommendations

Recommendations for use

- Mixable with DOT 3, as well as DOT 4 NON-SILICONE BASE products
- Do not mix with silicone (DOT 5.1 silicone base) or mineral base fluids (L-HM)
- Store fluid in original container, tightly closed to avoid absorption of moisture
- Never reuse drained brake fluid
- Brake fluid should be drained from the vehicle every 12 months or 24,000 miles (40,000 km) and refilled

Specifications and approvals

FMVSS 116
SAE J170 4
ISO 4925



Check Owner's Operator's Manual for details.

Partner with bproauto parts to provide your customers with a better driving experience.